



 SunTech® *Tango* M2
STRESS BP



Automated Blood Pressure Monitor
For Cardiac Stress and Exercise Testing



SunTech Tango M2

Our cardiac stress blood pressure (BP) monitoring products give you the confidence to know that patient movement, mechanical vibration and observer variability won't interfere with an accurate reading. Your focus can be where it matters most - on your patient.

Whether performing a test using a treadmill, ergometer, or pharmacological stress testing, the Tango M2 reliably monitors BP allowing you to focus on your patient. The Tango M2 was specifically designed to overcome noise, motion and physical difficulties associated with cardiac stress and exercise testing. The hands-free interface and SpO₂ measurement option make the Tango M2 a comprehensive cardiac testing center.

Recording an accurate and reliable BP measurement at the correct intervals during a test can be difficult and stressful for clinicians and lab technicians. That's why the Tango M2 can be programmed to take an accurate reading at the proper time and initiate readings at the precise moment during each stage, increasing reliability of the measurements. Designed to be used with our Orbit-K Cuff, the Tango M2 utilizes our proprietary DKA algorithm, which provides exceptional performance in the difficult environment of the stress lab.

Features & Benefits

Seamless Integration: Automated communication with your stress system reduces the risk of transcription errors.

Non-Exercise BP Mode: Allows BP measurement during patient set-up and recovery without an ECG signal.

Stat Mode: Rapidly repeated automatic BP measurements for time sensitive and emergent situations.

Color LCD: Improved usability with a 7" color LCD display.

Verified Measurements: See the Korotkoff sounds using the onscreen display.

Data Retrieval: Easier troubleshooting with 300 BP readings stored in memory and USB capabilities for measurement retrieval.

Field Upgrades: USB port allows for field upgrades, making sure end-users always have the current software.

Options

- Single Patient Use (SPU) Kits for increased infection control
- Pulse oximetry (SpO₂)
- Internal ECG

General Specifications

BP Measurement: Auscultatory R-wave gating using K-sound analysis, for all static & active phases of stress testing. Oscillometric using pneumatic pressure for static measurements only.

Measurement Range:

DKA Mode

Systolic: 40 - 270 mmHg Diastolic: 20 - 160 mmHg

OSC Mode

Systolic: 40 - 260 mmHg Diastolic: 20 - 160 mmHg

Heart Rate: 40 - 200 bpm

Interfaces: Integrates with all popular stress ECG systems using RS-232, BNC, ECG cable only for internal ECG & USB connections.

ECG Source: Primary - From integrated stress ECG system or other external source.
Secondary - Internal ECG option using V2, V6, RL

Power: Input - 100-240 VAC @ 1.5A, 50-60 Hz.
Output: +9 VDC @ 5A IEC 320 type input connector.
Classification - Class I, continuous

BP Sampling Intervals: From integrated stress ECG system or other external source, or 1-20 minute intervals.

Dimensions: 24.0 cm x 17.4 cm x 11.5 cm (9.5" x 6.9" x 4.5")

Weight: 1.68 Kg (3.725 lb)

Warranty: 2 year standard warranty on monitor.

Accuracy: Equivalent to a trained observer using a cuff/stethoscope auscultation method per ANSI/AAMI/ISO 81060-2

Standards: IEC 60601-1:2005, IEC 60601-1-2:2007 (EMC), IEC 80601-2-30:2009, ISO 80601-2-61:2011, ISO 10993-1:2009, ISO 10993-5:2009, ISO 10993-10:2010, FDA 21CFR801.5, MDD, WEEE



Orbit-K BP Cuffs

SunTech's patented Orbit-K™ BP cuff is designed specifically for cardiac stress and exercise testing applications. This sleeve enables the BP measurements to be repeatable and more reliable by maintaining proper BP cuff placement during the entire length of the cardiac stress test.

Orbit-K BP cuffs enable repeated, reliable BP measurements to be taken by maintaining proper placement for the length of the cardiac stress test while also ensuring patient comfort. The Orbit-K Cuff comes standard with our Tango M2 monitor and is designed to secure the microphone along the brachial artery.



With more than 30 years dedicated to developing our world-class blood pressure technology, we are confident that we don't miss a beat - so you won't either. It's our legacy. It's SunTech Medical. **It's The Difference In Clinical Grade.**



SunTech Medical, Inc.
507 Airport Boulevard, Suite 117
Morrisville, NC 27560-8200 USA
Tel: + 1.919.654.2300
1.800.421.8626
Fax: +1.919.654.2301
SunTechMed.com



EMERGO Europe
Prinsessegracht 20
2514 AP The Hague
The Netherlands

SunTech Medical (Shenzhen) Co., Ltd.
105 HuanGuan South Road, Suite 15 2~3/F
DaHe Community Guanlan,
LongHua District, Shenzhen
GuangDong PRC 518110
Tel.: + 86.755.29588810
+ 86.755.29588986 (Sales)
+ 86.755.29588665 (Service)
Fax: + 86.755.29588829
SunTechMed.com.CN



82-0126-00-MA RevG

SunTech Tango M2 Part Numbers

Tango M2 Systems

99-0088-00 Tango M2 without ECG
99-0088-01 Tango M2 with ECG

Contact customer service for a Tango M2 that interfaces with a specific stress system

Tango M2 Single Patient SPU Kits

*A disposable cuff solution for use on the SunTech Tango M2.
(12" K-sound Microphone not included with Kits)*

Small Adult SPU Kit Range 17-25 cm
Adult SPU Kit Range 23-33 cm
Adult Long SPU Kit Range 23-33 cm
Large Adult SPU Kit Range 31-40 cm
Large Adult Long SPU Kit Range 31-40 cm
12" SPU Kit K-sound microphone

Orbit-K Cuffs

Orbit-K™ Small Adult Cuff with microphone (18–27 cm)
Orbit-K Adult Cuff with microphone (25–35 cm)
Orbit-K Adult Plus Cuff with microphone (27–40 cm)
Orbit-K Large Adult Cuff with microphone (32–44 cm)

Accessories

Patient Cable. 15'
ECG Patient Cable (For Tango M2 with ECG)
RS-232 to USB Adapter Kit
LPXpod Kit
LPXpod Pulse with Adult Finger Clip Sensor
LPXpod Cable Oximeter
18" Orbit-K™ K-sound Microphone
Power Supply, 9V @ 5A 120/240V, Isolated Ground
Tango M2 Preventative Maintenance Kit
(Contains 1 Adult Plus cuff with microphone, 1 Adult Large cuff with microphone, and 1 Tango M2 Patient Cable)
Pole Clamp
Wrist Strap